

REDCOM SIGMA® 4.3 FEATURE LIST

Command & Control software from REDCOM

Features new to REDCOM Sigma 4.3 from version 4.2 are highlighted in yellow. Features marked with an asterisk (*) may require a feature license. Please contact your REDCOM sales representative for more details.

UNIFIED COMMUNICATIONS

- SIP (Trunking & Lineside)
- AS-SIP (Trunking & Lineside)
- Chat: XMPP with Presence
 - ◆ IRC Gateway
 - ◆ Archive messages
 - ◆ Federation with 3rd party servers
 - ◆ File transfer
 - ◆ Share rosters across federated networks
- Channels
- Conference
- FXO trunks (requires REDCOM FXO Adapter with XRI-400, SVG-1200, or XRI-M4K)
- RTP radio lines (unicast & multicast)
- Unified contact management
- Voice Mail*
 - ◆ Voice Mail to email
 - ◆ Sub-mailboxes
 - ◆ Message management
- Video (P2P)

SYSTEM FEATURES

- Announcements
 - ◆ Pre-recorded
 - ◆ Customer recordable
 - ◆ Localization
 - ◆ Per user
- Asynchronous DNS Lookup
- Auto Attendant/Direct Inward System Access (DISA)
- Automatic Failover
- Bandwidth Budgeting
- Broadcast Ringing Group
- Call Detail Records Configuration (SMDR/CDR/LAMA)
- Comfort Noise Generation
- Direct Inward Dial (DID)
- Direct Outward Dial (DOD)

- E.164 compliance
- Echo Cancellation
- In-band PTT functionality
- IPv4/IPv6 Dual-Stack
- Language app
- Network Tandem operation
- Silence Suppression
- SIP/SDP message manipulation
- Toll Restriction
- TSM™ Talk Group support*
- **Third-party call control API**

CALL FEATURES

- ANI Call Rejection
- Call Forwarding
- Call History
- Call Hold
- Call Waiting
- Call Transfer
- Caller ID Blocking
- Calling Name Delivery (CNAM)
- Do Not Disturb (DND)
- Find Me (Single Number Services)
- Hunt Groups (Percentage Trunking)
- Incoming Caller ID
- Message Waiting Indicator
- MLPP support on non-AS-SIP Lines
- Music on Hold
- Selective Call Acceptance
- Selective Call Rejection
- Simultaneous Ringing
- Speed Dialing
- Time and date feature control
- Transcoding
 - ◆ RFC 2833 / DTMF
 - ◆ Codecs
- Transrating
- Trunk registration and authentication

- Integrated support for REDCOM Secure Client

CUSTOMIZABLE CALL ROUTING

- Alternate routing
- Dialed number parsing
- Full URI analyzer for routing
- Incoming number parsing
- International Numbering Plans
- North American Numbering Plan compliance
- Private network numbering plans
- Routing by time and day
- Virtual Directory Number

C2 CONSOLE*

- Provides an operator with visibility of all connections & patches on a single screen
- Drag and drop connections together
- Listen & talk to patches & connections
- Monitor (output patches & connections to listen-only devices)
- In-app operator audio
- **Dial-in connections to C2 Console**

CHANNELS

- Ad-hoc channels
- Preconfigured channels
- **Selectable video streaming**
- **Spatial audio**
- **Priority members**
- **Security level support**

CONFERENCING

- Conference Bridges*
- Conference Modes
 - ◆ Meet-me
 - ◆ Pre-set
 - ◆ Blast Dial
 - ◆ Time of Day



RESEARCH, ENGINEERING, & DEVELOPMENT IN COMMUNICATIONS

ONE REDCOM CENTER, VICTOR, NY 14564, USA | 585.924.7550 | WWW.REDCOM.COM | SALES@REDCOM.COM

20250904

- Talker Priorities
- Conference Manager app*
 - ◆ Monitor and manage multiple conferences across several sites
 - ◆ Detailed attendee visibility & control
 - ◆ Conference video switching
- Security level announcements and reverse caller ID
- Robust access control by user ID, ANI, PIN code, or clearance level

PROVISIONING

- Centralized phone software updates
- Custom phone provisioning
- Device firmware management
- Provisioning for TEO, Grandstream, Polycom, Cisco, Snom, and Yealink phones
- Remote device management
- Setup Secure Client with QR codes

SIGMA XRI SUPPORT

- XRI radio support throughout the system and REST API
- Radio Port status app
- Radio net call control
- Radio net monitoring
- Donor radio detection on XRI ports
- Support for XRI-M4K module in a Klas Voyager system

OPERATION & ADMINISTRATION

- Software updates via ISO image, API, or from another Sigma install
- CSV upload and download
- DHCP Server
- External LDAP database support for user management
- LUA scripts for Media Server customization
- Network Diagnostics App
- Real-Time System Status Application
- REST API
- Security Logging
- SNMP support for alarms and system monitoring
- Syslog

REPORTING

- On-demand or scheduled
- Archived and/or distributed via email
- Reports can be exported to various file types, including PDF and Microsoft® Word

CODEC SUPPORT

- AMR
- G.711a 10/20/30/40ms
- G.711μ 10/20/30/40ms
- G.722 (HD) 10/20/30/40ms
- G.722.1 (HD) 24/32kbps 20/40ms
- G.723.1 6.3kbps send@30ms 5.3/6.3 receive@30ms
- G.726 16/24/32/40kbps at 10/20/30/40ms
- G.729ab 10/20/30/40ms
- iLBC 20/30ms
- MELP
- Opus
- Speex

SECURITY & ENCRYPTION

- ANI Lockdown
- FIPS 140-2 Certification
- HTTPS
- IPSec
- PKI (Public Key Infrastructure)
- SRTP
- OpenSSL 3.x
- Suite B
- TLS 1.3
- Password protection
- Private Certificate Authority (CA)
 - ◆ Create local CA within Sigma
 - ◆ Issuance; renewal and rekey; revocation services
- Remote authentication of users (i.e. RADIUS & LDAP)
- Single sign-on with browser certificates
- Subscriber PIN Access
- Online Certificate Status Protocol (OCSP)

SYSTEM

- Minimum system requirements
 - ◆ Intel® 64 Architecture
 - ◆ 2GB RAM
 - ◆ 40GB Disk Space

- Installation options
 - ◆ Bare Metal
 - ◆ Virtualized (i.e. VMware®, Hyper-V®, KVM, etc.)
- Included OS: Free BSD 14.2

SUPPORTED SIP-RELATED RFCS

- RFC 2833 – RTP Payload for DTMF
- RFC 3261 – SIP
- RFC 2976 – SIP INFO method (i.e. for SIP-Q)
- RFC 3262 – PRACK method, 100rel
- RFC 3263 – Server location
- RFC 3264 – Offer-answer model for SDP
- RFC 3265 – SUBSCRIBE/NOTIFY method, Events
- RFC 3311 – UPDATE method
- RFC 3323 – Privacy mechanism for SIP
- RFC 3326 – Reason header field – call complete elsewhere
- RFC 3515 – SIP REFER method
- RFC 3608 – SIP Extension header field
- RFC 3891 – Replaces header field
- RFC 3892 – Referred-by header field
- RFC 3903 – PUBLISH method
- RFC 4028 – SIP session timers
- RFC 4092 – ANAT in SIP
- RFC 5630 – SIP-SIPS
- RFC 5806 – Diversion Header
- RFC 5954 – Essential correction for IPv6 ABNF and URI comparison rules
- RFC 6140 – Registration for multiple phone numbers

SUPPORTED SDP-RELATED RFCS

- RFC 2327 – SDP
- RFC 3266 – Support for IPv6
- RFC 3605 – RTCP attribute in SDP
- RFC 4091 – Alternative Network Address Types (ANAT)
- RFC 4566 – SDP-new
- RFC 4568 – Security

SUPPORTED EVENT-PACKAGE RFCS

- RFC 3842 – Message waiting indication
- RFC 3856 – SIP extension for presence
- RFC 4235 – INVITE-initiated dialog

Some features are optional. ©2025 REDCOM Laboratories, Inc. REDCOM and Sigma are registered trademarks and the REDCOM logo is a trademark of REDCOM Laboratories, Inc. TSM is a trademark of TrellisWare Technologies, Inc. All other trademarks are property of their respective owners. Subject to change without notice or obligation. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (<http://www.openssl.org/>). This product includes cryptographic software written by Eric Young (ey@cryptsoft.com). This product includes software developed by the Computer Science Department at University College London.



RESEARCH, ENGINEERING, & DEVELOPMENT IN COMMUNICATIONS

ONE REDCOM CENTER, VICTOR, NY 14564, USA | 585.924.7550 | WWW.REDCOM.COM | SALES@REDCOM.COM

20250904